


Kühlung	
Toleranz	f8
Beschichtung	-



HA K203081



Stahl			Gehärteter Stahl				INOX (VA)	Guss	NE-Werkstoffe				Inconel	Abrasivmaterial		Titan
< 850 N/mm	< 1100 N/mm	< 1400 N/mm	< 55 HRC	< 60 HRC	< 67 HRC	< 70 HRC			Alu	Kupfer	Mg	Kunststoffe		CFK / GFK	Grafit	
70	50						45	75	190	160	240					

K203081	D1 mm ø	L2 mm	L1 mm	D2 mm ø	z #	r mm	 °
3	3,0	6,0	50,0	3,0	2	1,50	45
4	4,0	7,0	54,0	4,0	2	2,00	45
5	5,0	8,0	54,0	5,0	2	2,50	45
6	6,0	10,0	54,0	6,0	2	3,00	45
8	8,0	12,0	59,0	8,0	2	4,00	45
10	10,0	13,0	67,0	10,0	2	5,00	45
12	12,0	16,0	74,0	12,0	2	6,00	45
14	14,0	16,0	75,0	14,0	2	7,00	45
16	16,0	20,0	83,0	16,0	2	8,00	45
20	20,0	25,0	93,0	20,0	2	10,00	45